

Principal dimensions (mm)			Basic load KN		Pu	Speed ratings rpm		Bearing + Withdrawal sleeves	Designation		Dimensions mm										Abutment and fillet mm			Value			
d <sub>1</sub>	D	B	dyc Cr	stc Cor		Speed Ratings	Limiting g		Bearing	Withdrawal sleeves	d <sub>1</sub>	d <sub>2</sub> ~	D1 ~	B <sub>1</sub>	B <sub>2</sub> <sup>1)</sup>	G	G <sub>1</sub>	b	k	r <sub>1,2</sub> Min	d <sub>a</sub> Max	Da Max	r <sub>a</sub> Max	e	Y1	Y2	Y <sub>o</sub>
85	160	52.4	355	440	48	2800	3800	5.00	*23218CCK/W33	AHX3218	85	106	137	63	67	M100×2	10	5.5	3	2	101	149	2	0.31	2.2	3.3	2.2
95	180	60.3	475	600	63	2400	3400	7.30	*23220CCK/W33	AHX3220	95	117	153	73	77	M110×2	11	8.3	4.5	2.1	112	168	2	0.33	2	3	2
105	200	69.8	600	765	76.5	2200	3200	10.5	*23222CCK/W33	AHX3222G	105	130	169	82	86	M120×2	11	8.3	4.5	2.1	122	188	2	0.33	2	3	2
115	215	76	695	930	93	2000	2800	13.0	*23224CCK/W33	AHX3224G	115	141	182	90	94	M130×2	13	8.3	4.5	2.1	132	203	2	0.35	1.9	2.9	1.8
115	260	86	965	1120	100	2000	2600	24.0	*23224CCK/W33	AHX3224G	115	152	216	105	109	M130×2	17	13.9	7.5	3	134	246	2.5	0.35	1.9	2.9	1.8
125	230	80	780	1060	104	1900	2600	15.5	*23226CCK/W33	AHX3226G	125	151	196	98	102	M140×2	15	8.3	4.5	3	144	216	2.5	0.33	2	3	2
125	280	93	1120	1320	114	1800	2400	30.5	*23226CCK/W33	AHX3226G	125	164	233	115	119	M140×2	19	16.7	9	4	147	263	3	0.35	1.9	2.9	1.8
125	280	93	1120	1320	114	1800	2400	30.5	*23226CCK/W33	AHX3226G	125	164	233	115	119	M140×2	19	16.7	9	4	147	263	3	0.35	1.9	2.9	1.8
135	250	88	915	1250	120	1700	2400	20.5	*23228CCK/W33	AHX3228G	135	165	212	104	109	M150×2	15	11.1	6	3	154	236	2.5	0.33	2	3	2
135	300	102	1290	1560	132	1700	2200	38.0	*23228CCK/W33	AHX3228G	135	175	247	125	130	M150×2	20	16.7	9	4	157	283	3	0.35	1.9	2.9	1.8
145	270	96	1080	1460	137	1600	2200	26.0	*23230CCK/W33	AHX3230G	145	175	228	114	119	M160×3	17	11.1	6	3	164	256	2.5	0.35	1.9	2.9	1.8
150	290	80	1000	1290	118	2000	2800	25.0	*23232CCK/W33	AH3132G	150	191	250	103	108	M170×3	16	13.9	7.5	3	174	276	2.5	0.26	2.6	3.9	2.5
150	290	104	1220	1660	153	1500	2200	34.5	*23232CCK/W33	AH3232G	150	188	244	124	130	M170×3	20	13.9	7.5	3	174	276	2.5	0.35	1.9	2.9	1.8
160	310	110	1400	1930	173	1400	2000	41.0	*23234CCK/W33	AH3234G	160	200	261	134	140	M180×3	24	13.9	7.5	4	187	293	3	0.35	1.9	2.9	1.8
170	320	112	1500	2120	186	1300	1900	43.5	*23236CCK/W33	AH3236G	170	211	271	140	146	M190×3	24	13.9	7.5	4	197	303	3	0.35	1.9	2.9	1.8
180	340	120	1660	2400	208	1300	1800	52.5	*23238CCK/W33	AH3238G	180	222	287	145	152	M200×3	25	16.7	9	4	207	323	3	0.35	1.9	2.9	1.8
190	360	128	1860	2700	228	1200	1700	63.0	*23240CCK/W33	AH3240	190	235	304	153	160	Tr220×4	25	16.7	9	4	217	343	3	0.35	1.9	2.9	1.8
200	400	144	2360	3450	285	1100	1500	93.0	*23244CCK/W33	AOH2344	200	259	338	181	189	Tr240×4	30	16.7	9	4	237	383	3	0.35	1.9	2.9	1.8
220	440	160	2900	4300	345	950	1300	120	*23248CCK/W33	AOH2348	220	286	374	189	197	Tr260×4	30	22.3	12	4	257	423	3	0.35	1.9	2.9	1.8
240	480	174	3250	4750	360	850	1200	155	*23252CCK/W33	AOH2352G	240	312	408	205	213	Tr280×4	30	22.3	12	5	280	460	4	0.35	1.9	2.9	1.8
260	500	176	3250	4900	365	800	1100	160	*23256CCK/W33	AOH2356G	260	332	429	212	220	Tr300×4	30	22.3	12	5	300	480	4	0.35	1.9	2.9	1.8
300	540	192	3900	5850	425	750	1000	200	*23260CCK/W33	AOH3260G	300	356	461	228	236	Tr320×3	34	22.3	12	5	320	520	4	0.35	1.9	2.9	1.8
320	580	208	4400	6700	480	700	950	250	*23264CCK/W33	AOH3264G	320	382	493	246	254	Tr340×3	36	22.3	12	5	340	560	4	0.35	1.9	2.9	1.8